





INSTALLATION

- 1 DISCONNECT your vehicle's negative (-) battery cable.
- 2 MOUNT your gauge to the panel using the spin lock ring.
- 3 CONNECT the gauge wiring.
- **4** RECONNECT your vehicle's negative (-) battery cable.

ANTENNA CONNECTION

- 1. Hook up speedometer power requirements as shown.
- 2. Thread on GPS receiver antenna into the back of the speedometer. (Make sure it is threaded on all the way for a good connection.)
- 3. For best performance, mount GPS antenna with as much view of sky as possible (preferebly on the roof of the vehicle). The GPS antenna is waterproof and magnetic. If the car's roof is not accessible then mount the antenna on top of the vehicle's dash with as much exposure as possible to the sky through the window. (Antenna is able to receive signal through some thin material i.e. wood, glass, fiberglass, and plastic. All types of metal will block the signal.)
- 4. Pointer will bounce at zero until the GPS signal is acquired.

CONTACT US

Support@Speedhut.com 801-221-1460 (9a-4p MST) FAQ - Speedhut.com/faq.i www.Speedhut.com

LIFETIME WARRANTY

We take pride in the products we make and offer a Lifetime Warranty on gauge electronics and a 5-year warranty on hardware for every gauge, tachometer and shift light purchased since Jan 1, 2006. Every SPEEDHUT product is built for a lifetime of service, and we warrant to the person who originally purchased the product that all SPEEDHUT products will be free from defects in workmanship and materials for their applicable warranty period. If a defect occurs during the warranty period as the result of the product's intended use, we will repair or replace the defective product or part, to our discretion. The warranty does not cover defects caused by third-party modifications, repairs or replacement parts. Any holes, scratches, normal wear and tear, and the natural breakdown of colors and materials over extended time and use are not warranted.